

Ecosurface ProBasePad™ - playground shock pads

Product description

Ecosurface ProBasePad is a 100% pure polypropylene, interlocking, shock absorbing pad that is designed to work as a base layer underneath the Ecosurface

bonded mulch system. Working directly with the manufacturer Ecosurface have exclusive distribution arrangements in place and can despatch direct from the ISO-certified facility in Holland, or our UK distribution centre.

The life expectancy of the ProBasePads is over 25 years, and will not decay or degrade over time and is resistant to bacteria, fungi and chemicals. It is 100% lead free, 100% non toxic and in the future is expected to be reused or can be 100% closed-loop recyclable.

The pads are engineered and designed specifically for playground safety, which are individually quality controlled to ensure consistent performance and predictable safety and precise fit regardless of temperature, or age.

Each pad has a series of Impact-absorbing pistons on the bottom, which also offer excellent vertical and lateral drainage capability.

When to use

The established bonded Ecosurface rubber mulch system is designed to be used directly over natural grass or soil without the need for any foundations or base layers, and is tested under EN1177 procedures to meet most critical fall height requirements.

However there may be occasions where the rubber mulch is required to be laid directly over a solid base, such as concrete, and then the combined use of the ProBasePad as a shock layer underneath the Ecosurface bonded rubber mulch will give improved fall height protection.



Certificates to EN1177 standard are available on request.

Best choice

Compared to other base layer options, the ProBasePad allows for cheaper, quicker installation with less damage to the natural environment and at no time has any landfill costs or environmental consequences.



How to use Ecosurface ProBasePad shock system



ProBasePads install directly onto the ground with no additional ground excavation, and when used with the Ecosurface bonded rubber mulch require no edging materials or defined borders

The pads do not need to be secured to a solid floor; the pads will simply interlock without the need for glues or tapes and they have been engineered as a dimensionally stable system that can be installed in virtually any climatic condition, and they include a unique interlocking arrangement that allows for thermal movement even once installed.

Cutting shapes or around posts is easily done with a simple sharp knife so it will add very little time to create the ground cover which is immediately available for the top covering of Ecosurface rubber mulch.

Ecosurface, Walton Moore Ltd, PO Box 475, Bicester, Oxon, OX26 9NQ, UK

Tel: + 44 (0) 1869 457070

E-mail: info@ecosurface.co.uk

Web: www.ecosurface.co.uk

Ecosurface is a trading name of Walton Moore Ltd